



## Sullair Performance Lubricant

# SULLAIR SRF II/8000<sup>®</sup>

### Standard Replacement Fluid for Stationary Compressors



SRF II/8000 is a highly refined standard replacement fluid for stationary air compressors. This long-life hydro-treated petroleum-based fluid helps reduce maintenance, operation and disposal costs.

- Lasts long – up to 8000 hours or one year
- Resists breakdown from shearing and high temperatures

#### **High quality — value priced**

*With excellent viscosity, SRF II/8000 is a high quality fluid offering high resistance to breakdown for stable operation at a wide range of temperatures. A hydro-treated fluid, it is highly demulsifiable, increasing the efficiency of oil/condensate separators. And SRF II/8000 is a good value for the money – providing budget-friendly long life.*

## FEATURES AND BENEFITS

#### **Long lasting**

Hydro-treated petroleum base resists breakdown and varnish.

#### **Lubricates effectively**

Excellent anti-wear properties are designed to provide longlasting lubrication.

#### **Lowers expenses**

Long changeout intervals cut maintenance labor and fluid disposal costs. Non-hazardous classification of used fluid reduces disposal costs further.

#### **Comprehensive support**

Sullair and our distributors stand ready with fluid professionals who can help you with any fluid-related issues or questions. Our exclusive Compressor Fluid Analysis program helps you evaluate your fluid and provides data to support your lubricant performance history, changeout intervals, and environmental conditions that may affect your fluid.

# PRODUCT INFORMATION



PACKAGING	
Size	Part Number
5 Gallon	02250118-160
55 Gallon	02250118-162

TYPICAL PROPERTIES		
Viscosity	104°F (40°C)	35.6
	212°F (100°C)	5.7
Flash Point	431°F (222°C)	
Hours	8000	



FOR MORE INFORMATION, CONTACT YOUR LOCAL AUTHORIZED SULLAIR DISTRIBUTOR.



SULLAIR.COM   