



# SULLAIR SP7

## OIL WATER SEPARATOR



**An easy, convenient, clean and cost-effective solution to filter condensate discharge and keep your compressor room EPA compliant.**

- Unique size
  - 35 lbs new and 65 lbs full
  - Easy to manage
  - Small footprint
- Maintenance free
  - No need to ever open the unit
  - No pumps, sensors, or pre-separation filter pads
  - Not susceptible to mold
  - No messy element to change
- No power consumption
  - No electricity needed
  - Internal decompression chamber
  - Place anywhere
- <10 ppm carryover
  - Separates emulsified condensate
  - Disposal as non-hazardous special waste
- Easy installation and change out
  - Prime unit and run condensate lines directly into unit
  - Saves time and mess for service
  - When full, replace with a new unit
- Works with ALL Compressor Fluids
  - Manages all compressor fluids including POLYGLYCOL and SILICONE
  - Alumina silicate substrate media bed
  - Specific gravity, emulsification, and relative humidity do not affect performance

# TECHNICAL SPECIFICATIONS

FOR MORE INFORMATION, CONTACT YOUR LOCAL AUTHORIZED SULLAIR DISTRIBUTOR.



COMPRESSOR HP	SP7 LIFE - HOURS
5-15	16,000
20-40	8,000
50-75	6,000
100-150	4,000
200+	2,000

SPECS	
Inlet / Outlet inches	0.25 / 0.75
Outlet inches	0.75
Height inches	25
Width / Depth inches	15
Max Flow gpm	2
Max Temp °F	125