



## Sullair Performance Lubricant **SULLAIR SRF PLUS**



SRF Plus is a synthetic Polyglycol-based compressor lubricant designed for rotary screw air compressors, of any manufacturer. This 8000-hour Polyglycol Synthetic blend resists varnish and sludge.

- Up to 8000 hours or one year, whichever comes first
- Resists sludge and varnish
- High viscosity index

### **POLYGLYCOL BASED — VALUE PRICED**

SRF Plus is a high quality Polyglycol Synthetic blend offering high resistance to breakdown for stable operation at a wide range of temperatures. SRF Plus is a good value for the money – providing a budget-friendly alternative.

### **FEATURES AND BENEFITS**

#### **Long Lasting**

Polyglycol Synthetic blend lasts up to 8000 hours.

#### **Lubricates Effectively**

Excellent anti-wear properties are designed to provide long-lasting lubrication.

#### **Resists Varnish and Sludge**

Designed with a high-quality hydro treated hydrocarbon and Polyglycol Synthetic (Pag-Syn) lubricant blend designed to resist varnish and sludge in normal environments.

#### **Comprehensive Support**

Sullair and our distributors stand ready with fluid professionals who can help you with any fluid-related issues or questions. Our exclusive Compressor Fluid Analysis program helps you evaluate your fluid and provides data to support your lubricant performance history, changeout intervals, and environmental conditions that may affect your fluid.

# PRODUCT INFORMATION



PACKAGING	
Size	Part Number
5 Gallon	02250251-252
Skid (48ct) 5 Gallon	02250251-253

TYPICAL PROPERTIES		
Viscosity	40°C	39.8 - 51.5
	104°F	39.8 - 51.5
Flash Point	428°F (220°C)	
Hours	Up to 8,000 hours	



FOR MORE INFORMATION, CONTACT YOUR LOCAL AUTHORIZED SULLAIR DISTRIBUTOR.



SULLAIR.COM   